



# VILLAGE OF WILLIAMS BAY

## STREET OPENING PERMIT

Driveways   Streets   Water/Sewer   Right-of-way   Sidewalks

### Applicant Information

Name \_\_\_\_\_

Address \_\_\_\_\_

Phone Number \_\_\_\_\_

### Contractor Information

Company Name \_\_\_\_\_

Contact Name \_\_\_\_\_

Address \_\_\_\_\_

24 Hr. Emergency Contact Phone Number \_\_\_\_\_

WI Credential/License Type \_\_\_\_\_ License Number \_\_\_\_\_

INSURANCE- Include a current certificate of insurance or official note of insurance.

### Property Information

Owners Name \_\_\_\_\_

Property Address \_\_\_\_\_

Phone Number \_\_\_\_\_

### Worksite Information

Type of work being performed \_\_\_\_\_

Start Date \_\_\_\_\_ Finish Date \_\_\_\_\_



# VILLAGE OF WILLIAMS BAY

## STREET OPENING PERMIT REQUIREMENTS

THESE GUIDELINES MUST BE FOLLOWED FOR ALL STREET OPENINGS.

**\*\*\* \$50.00 Fee Must Accompany Application\*\*\***

1. All traffic control and barricading, done to Village's satisfaction, is the responsibility of the contractor.
2. Contractor must use depth saw cut.
3. Entire trench must be backfilled with granular backfill or slurry if required by the Director of Public Works. If trench is filled with granular fill, ditch must be compacted and allowed to settle for a minimum of one month, paving can commence after Director of Public Works gives approval. During cold seasons the contractor must fill the street with cold patch until warmer weather when the permanent repair can be made.
4. The attached **Water and Sewer Specifications** must be adhered to.
5. Contractor will be responsible for any excavation if their repair should fail. Contractor is responsible for their work and dig site for up to 12 months including road surface repair.
6. All water and sewer services new or abandoned must be inspected by the Director of Public Works or Village personal, during the hours Monday thru Thursday 7AM to 3PM. Notice must be given prior to digging that an inspection will be needed.
7. Permits must be received a minimum of 5 working days prior to the start of work.  
***Return completed forms to Village Hall or email [wedwards@vi.williamsbay.wi.gov](mailto:wedwards@vi.williamsbay.wi.gov).***
8. Any questions regarding the street opening guidelines should be made to the Director of Public Works at 262-903-1764.
9. Property owner will be responsible for all repairs made to the street. Repairs will be done in accordance to Village specifications. If repairs are not made within the schedule set by the Director of Public Works, the Village will make such repairs and invoice the cost of same to the property owner. Failure to pay these charges by their due date will result in a lien against the property for collection of same.

\_\_\_\_\_  
SIGNATURE OF PROPERTY OWNER

\_\_\_\_\_  
DATE

\_\_\_\_\_  
SIGNATURE OF CONTRACTOR

\_\_\_\_\_  
DATE

\_\_\_\_\_  
VILLAGE APPROVAL

\_\_\_\_\_  
DATE

**VILLAGE OF WILLIAMS BAY**

**PO Box 580  
155 Elkhorn Rd.  
WILLIAMS BAY, WI 53191  
(262) 245-2700**

**January 7, 2019**

**WATER AND SANITARY SEWER MAIN SPECIFICATIONS**

<b>Director of Public Works:</b>	<b>Wayne Edwards (262) 245-2706</b>
<b>Consulting Engineer:</b>	<b>Baxter Woodman 256 South Pine Street Burlington, WI 53105 (262) 763-7834 Doug Snyder</b>
<b>Watermain:</b>	<b>CL-52 Ductile Iron Pipe or AWWA Cast Iron O.D. C-909 PVC Water Pipe with 10ga Blue Tracer Wire and Tracer Wire Access Boxes</b>
<b>Watermain Fittings:</b>	<b>Compact Ductile Iron Mechanical Joint Fittings with Cor-Blue or 304 SS Nuts and Bolts Must Be American Made AWWA-C-153</b>
<b>Gate Valves:</b>	<b>4-12" Mueller A2361 Resilient Wedge Valve 2" Sq. Nut Open Left No Alternates Allowed</b>
<b>Butterfly Valves:</b>	<b>14" And Larger Mueller B3211-20 or Pratt Mechanical Joint Butterfly Valve AWWA C504 2" Sq. Nut Open left No Alternates Allowed</b>
<b>Fire Hydrants:</b>	<b>A423 Mueller Centurion Hydrant 6' Trench Depth, 6" MJ Shoe 1 1/2" Pentagon Operating Nut, Open Left, National Standard Nozzles, with 5" Storz Connection Painted Red No Alternates Allowed</b>  <b>All Hydrant Parts &amp; Extensions Must Be Original Manufacturer Parts</b>

**Valve Boxes & Adapter:**

**664S Cast Iron Two Piece Box  
Must Be American Made**

**Rubber Valve Box Adapter Shall  
Be Valve Box Adapter II  
Manufactured By Adapter, Inc.  
No Alternates Allowed**

**Tapping Sleeve & Valves:**

**Mueller H615 Mechanical Joint  
Tapping Sleeve W/Mueller A2361  
Flg X MJ Resilient Wedge Valve  
No Alternates Allowed.**

**#665 Smith Blair Stainless Steel  
Tapping Sleeve acceptable Only in  
Vaults or if in Non-Paved location**

**Repair Clamps:**

**#226 Smith Blair Repair Clamp  
With Stainless Steel Bolts & Nuts**

**Water Service Lines:**

**SDR 9 Polyethylene Tubing (CTS)  
250 PSI AWWA C901  
with Stiffeners & 12ga Tracer Wire**

**1" Water Service Fittings:**

**1" H-15008 Mueller Compression  
Corporation Stop  
1" H-15155 Mueller Compression  
Curb Stop  
6" H-10300 Mueller Curb Box  
~~1 1/2" H-15013 Mueller~~  
No Alternates Allowed**

**1 1/2 and 2" Water Service Fittings:**

**1 1/2-2" H-15013 Mueller  
Compression Corporation Stop  
1 1/2-2" B-25155 Mueller  
Compression Curb Stop  
6" H-10300 Mueller Curb Box  
~~1 1/2" H-15013 Mueller~~  
~~#317 Smith Blair Epoxy Coated~~  
Saddle W/Stainless Steel Straps  
or JCM Equal**

**Sanitary Sewer Pipe:**

**SDR 26 ASTM D-3034**

**Sanitary Sewer Laterals:**

**SDR 26 ASTM D-3034**

**Service Fittings:**

**Gasket Joint Wye Fittings  
W/45° Bend ASTM D-3034**

**Manhole Covers:**

**1050 East Jordan Frame with  
1020 Cover or equal in Roadway**

**1020 East Jordan Frame with  
1020 Cover or equal off Roadway**