



1151 W Main Avenue
DePere, WI 54115
Sales Rep: Eric Krahenbuhl
Ph: (262) 269-6322
www.MonroeTruck.com

J.O. #

Quotation ID: 2CHK001076-1

Date: 1/4/2021

Valid thru: 2/3/2021

Terms: NET 30

Quoted by: Clayton Kraft

Ph/Fax: 920-347-4189 / 920-336-8118

Quoted to:

WILLIAMS BAY, VILLAGE OF (ATTN:)
250 WILLIAMS ST
WILLIAMS BAY, WI 53191
Ph: 262-245-2703 / Fax: 262-245-2705

Email:

Chassis Information

Year: 2020	Make: INTERNATIONAL	Model: CV SERIES	Chassis Color:	Cab Type: REGULAR
Single/Dual: DRW	CA: 84.0	CT: -1.0	Wheelbase: 165.0	Engine: DIESEL
			F.O. Number #:	Vin:

Notes:

Monroe Truck Equipment, Inc. is pleased to offer the following quote for your review:

Description	Amount
-------------	--------

MONROE SNOW FIGHTER PACKAGE

CRYSTEEL 9' STAINLESS STEEL RIGID SIDE DUMP BODY

- 1/4" INTEGRAL CABSHIELD
- 87 ID
- 96 ID
- 46" 10 GA 201 STAINLESS STEEL FRONT
- 20" 12 GA 201 STAINLESS STEEL SIDES
- 26" 10 GA 201 STAINLESS STEEL TAILGATE
- 10 GA 201 STAINLESS STEEL FLOOR
- DOUBLE PANEL QUICK DROP TAILGATE
- WESTERN TUBULAR FRAME
- ***NO WINDOW***
- FMVSS108, L.E.D. LIGHTS AND REFLECTORS WITH WEATHER-RESISTANT WIRING HARNESS
- 2-1/2" HEAVY DUTY RECEIVER HITCH IN 1/2" PLATE WITH CHAIN LOOPS AND ICC BUMPER
- STAINLESS STEEL SPRING LOADED SHOVEL HOLDER MOUNTED ON DRIVER SIDE MID BODY BOARD SUPPORT
- ELECTRIC BACKUP ALARM 97DB
- POLY FENDERS

SUBFRAME SCISSOR HOIST

- FULL LENGTH HEAVY DUTY SUBFRAME
- BODY PROP TO SUPPORT EMPTY BODY
- BODY-UP LIGHT

MONROE HYDRAULICS PKG WITH FORCE AMERICA SSC5100EX SPREADER CONTROL (STAINLESS STEEL)

- 12.5 GP MANIFOLD VALVE ASSY
- OPEN CENTER, 2500 P.S.I. PRE-SET SYSTEM RELIEF, 20 GPM CAPABLE
- PRIORITY FLOW FOR PLOW
- DOUBLE ACTING ELECTRIC PROPORTIONAL CONTROL HOIST SECTION WITH A 500 P.S.I. DOWN PORT RELIEF
- BOSS DOUBLE ACTING ELECTRIC CONTROL PLOW LIFT WITH FLOAT & SMART HITCH
- BOSS DOUBLE ACTING ELECTRIC PROPORTIONAL CONTROL PLOW ANGLE
- ELECTRIC PROPORTIONAL AUGER FUNCTION, 14 GPM
- ELECTRIC PROPORTIONAL SPINNER FUNCTION, 5 GPM

HYDRAULIC RESERVOIR/ENCLOSURE

- 13 GALLON CAPACITY
- FILLER/BREATHING CAP, LEVEL/TEMP SIGHT GLASS, 3/4" MAGNETIC PLUG
- IN-TANK FILTER, 10 MICRON, 60 P.S.I. CONDITION INDICATOR
- IN-TANK BAFFLE
- VALVE WILL BE INSTALLED IN A WEATHER-TIGHT COMPARTMENT ON RESERVOIR
- HYDRAULIC RESERVOIR/ENCLOSURE WILL BE MOUNTED ON FRAME RAIL
- STAINLESS STEEL

CONTROLS

- DASH MOUNTED MOMENTARY ROCKER SWITCH FOR HOIST CONTROL



FORCE SSC5100EX SPREADER CONTROL

- MAINTAINS CONSTANT APPLICATION BASED ON VEHICLE SPEED
- EASILY CHOOSE BETWEEN MANUAL AND GROUND-BASED SPREADING APPLICATIONS
- CREATES REPEATABLE PRECISE CONTROL OF SPREADER AND SPINNER SETTINGS
- INTEGRATED SPINNER/BLAST DIALS THAT PROVIDE SIMULTANEOUS SPINNER ADJUSTMENT WHILE BLAST IS ACTIVATED
- A MOMENTARY OR TIMED PREFERENCE CAN BE TAILORED FROM 0-15 SECONDS FOR THE INDIVIDUAL OPERATOR
- SELECTABLE VALVE DRIVE FREQUENCY
- OPERATE SPREADER STANDBY AND BLAST FUNCTIONS THROUGH FRONT PANEL
- MANUAL RESET CIRCUIT BREAKERS
- REVERSE POLARITY AND OVER-VOLTAGE PROTECTION
- COLOR-CODED WIRING
- MOUNTED WITHIN EASY REACH OF OPERATOR

MISCELLANEOUS HOSES & FITTINGS

- HYDRAULIC HOSES & FITTINGS; RUN TO REAR FOR SPREADER
- HYDRAULIC HOSES & FITTINGS; PTO MOUNTED KIT
- MANIFOLD PLATE, RUBRAIL MOUNTED (BOTH SIDES); INSTL
- DUST COVERS FOR ALL QUICK COUPLERS

INSTALLED

FAN BELT DRIVEN HYDRAULIC PUMP

PRESSURE RELIEF - REQUIRED FOR USE W/ FAN BELT KIT WHEN PLOW OR WING ARE POWERED BY CENTRAL HYDRAULICS SYSTEM

10' BOSS POWER-V-DXT SNOWPLOW WITH JOYSTICK CONTROLLER

- HIGH PERFORMANCE HYDRAULIC PACKAGE
- ENCLOSED HYDRAULICS
- CHAINLESS HYDRAULIC CYLINDER LIFTING SYSTEM
- DUAL-TRIP DESIGN
- FLARED WINGS
- RUBBER SNOW DEFLECTOR
- REINFORCED MOLDBOARD
- HEAVY-DUTY PUSH FRAME AND QUADRANT
- CUTTING EDGE KIT
- INSTALLED
- TWO-YEAR LIMITED WARRANTY

MONROE 6" ONE-WAY FLIGHT UNDER-TAILGATE SPREADER

STANDARD EQUIPMENT:

- 7 GA. TROUGH
- 1/4" END PLATES
- FULL OPENING TOP AND BOTTOM CLEAN-OUT DOORS
- 6" AUGER DIAMETER
- DUAL DISCHARGE
- STAINLESS STEEL QUICK DETACH MOUNTING BRACKETS
- STAINLESS STEEL TAILGATE SHIELDS
- BARE STAINLESS FINISH (NOT PAINTED)
- 18" POLY SPINNER DISC
- SELF LEVELING SPINNER ASSEMBLY WITHOUT STABILIZER RODS
- LIGHT BAR KIT
- INSTALLED

LIGHTING AND ELECTRICAL

- 7-WAY CONNECTOR, ROUND SOCKET, FLAT PIN, RV STYLE
- MONROE/WHELEN RESPONDER SERIES L.E.D. MINI LIGHT BAR; AMBER; MTR1LPPA
- SELF-LEVELING BRACKET FOR MINI LIGHT BAR
- (2) VTX609A STROBES ON REAR CORNER POST ABOVE STOP/TAIL/TURN LIGHTS
- ALL BODY LIGHTS TO BE L.E.D.
- L.E.D. CLEAR SPREADER LIGHT MOUNTED ON SPREADER W/ WEATHER PACK CONNECTOR

MONROE LDS-333 ELECTRIC TRUCK MOUNTED LIQUID DISPENSING SYSTEM

STANDARD EQUIPMENT:

- ELECTRIC 12 VDC SEALED 3 GPM PUMP/MOTOR COMBINATION W/ INTEGRAL PUMP SHUT-OFF SWITCH ALL WITHIN SEALED NEMA FIBERGLASS ENCLOSURE
- TWO (2) 1 GPM BRASS SPRAY NOZZLES, STRAINER AND HOSES FOR APPLYING LIQUID
- 120 GALLON POLY TANK
- SPRAY BAR KIT
- FLUSH KIT

Description	Amount
- BULK FILL KIT	
- INSTALLED	

Quote Total: \$50,017.00

Additional Options:

Description	Amount	Add to quote? Yes / No
-------------	--------	---------------------------

Terms & Conditions

- Terms are Due Upon Receipt unless prior credit arrangements are made at the time of order.
- Please note if chassis is furnished, it is as a convenience and terms are Net Due on Receipt of Chassis.
- State and Federal taxes will be added where applicable. **Out-of-state municipal entities may be subject to Wisconsin sales tax.**
- Restocking fees may be applicable for cancelled orders.
- MTE is not responsible or liable for equipment that does not meet local/state regulations if those laws are not made known at time of order.

By signing and accepting this quote, the customer agrees to the terms listed above and has confirmed that all chassis information listed above is accurate to chassis specs.

Re-Assign (Required for all pool units):	<input type="checkbox"/> Fleet	<input type="checkbox"/> Retail	Customer P.O. Number:	Dealer Code:	Sourcewell Member Number:
MSO/MCO (ONLY check if legally required):	<input type="checkbox"/> MCO	<input type="checkbox"/> MSO			
Customer Signature:				Date of Acceptance:	

